

**Other designs in series 25**

The following other designs can be found from page:

- | | |
|-----------------------|--------|
| ► Stainless Steel | P. 208 |
| ► Safety | P. 274 |
| ► Safety Self-Venting | P. 294 |
| ► Coded Systems | P. 302 |

Technical Description

Universal industrial coupling with standard European profile.

Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use.

Dust Protections (P. 319)

for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S

Working Temperature*

-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with safety factor 4 to 1.



35 bar



8 bar

Features

- Brass coupling and plug for use with water
- Robust coupling system with steel sleeve

- Minimal, almost imperceptible leakage when uncoupling
- No air locked into the system during the coupling process
- Brass valved plug available blank

Material







Coupling: Brass / Steel nickel plated
Plug: Steel zinc plated or Brass (Serie 26)
Seals: NBR

Coupling: Brass
Plug: Brass
Seals: NBR







Coupling: Brass nickel plated
Plug: Brass nickel plated
Seals: NBR

Interchangeability

- Rectus 26
- Rectus 1600/1625
- Cejn 320
- JWL 520 + JWL 530
- various German Products

Flow diagrams







	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	R 1/4	19		60	12		23				25KAAK13MPN
	R 3/8	19		60	12		23				25KAAK17MPN
	R 1/2	22		61	17		23				25KAAK21MPN
	M 14 x 1,5	19		59	10		23				25KAAD14MPN
	M 16 x 1,5	19		60	11		23				25KAAD16MPN
	M 18 x 1,5	19		60	11		23				25KAAD18MPN
 Female Thread	G 1/4	19		56	10		23				25KAIW13MPN
	G 3/8	19		55	9		23				25KAIW17MPN
	G 1/2	24		58	12		23				25KAIW21MPN
	M 14 x 1,5	19		55	9		23				25KAIM14MPN
	M 16 x 1,5	19		55	9		23				25KAIM16MPN
	M 18 x 1,5	22		56	9		23				25KAIM18MPN
 Hose Barb	6 mm	19		74	25		23				25KATF06MPN
	8 mm	19		74	25		23				25KATF08MPN
	9 mm	19		74	25		23				25KATF09MPN
	10 mm	19		74	25		23				25KATF10MPN
	13 mm	19		74	25		23				25KATF13MPN
	6 mm Parker	19		69	20		23				25KATP06MPN
	10 mm Parker	19		73	24		23				25KATP10MPN
	13 mm Parker	19		76	28		23				25KATP13MPN
 with Plastic Hose Connection	6 x 8 mm	19		61	7	6	23		M 12 x 1		25KAKO08MPN
	8 x 10 mm	19		65	9	8	23		M 16 x 1		25KAKO10MPN
	9 x 12 mm	19		65	9	8	23		M 16 x 1		25KAKO12MPN
 Panel Mount with Hose Barb	6 mm	19	17	76	17	10	23	4	M 12 x 1		25KATS06MPN
	8 mm	19	17	80	17	14	23	4	M 12 x 1		25KATS08MPN
	10 mm	19	17	87	25	14	23	4	G 1/4		25KATS10MPN
 Plastic Hose Connection with Spring Guard	6 x 8 mm	19		144	7	6	23		M 12 x 1		25KAKK08MPN
	8 x 10 mm	19		155	9	8	23		M 16 x 1		25KAKK10MPN
	9 x 12 mm	19		162	9	8	23		M 16 x 1		25KAKK12MPN







Plugs – without valve

Series 25KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	R 1/8	13		33	9						25SFAK10SXZ
	R 1/4	14		36,5	12						25SFAK13SXZ
	R 3/8	17		37	12						25SFAK17SXZ
	R 1/2	22		43	17						25SFAK21SXZ
	M 14 x 1,5	17		35	10						25SFAD14SXZ
	M 16 x 1,5	19		36	11						25SFAD16SXZ
	M 18 x 1,5	22		37	11						25SFAD18SXZ
 Female Thread	G 1/8	14		30	5						25SFIW10SXZ
	G 1/4	17		38,5	12						25SFIW13SXZ
	G 3/8	19		39,5	12						25SFIW17SXZ
	G 1/2	24		44	14						25SFIW21SXZ
	M 14 x 1,5	17		33	8						25SFIM14SXZ
	M 16 x 1,5	19		33	10						25SFIM16SXZ
	M 18 x 1,5	22		36	13						25SFIM18SXZ
 Flex Joint, Male Thread	R 1/4	17		64	11					nickel plated	25FAAK13SPN
 Hose Barb	6 mm			48	25		12				25SFTF06SXZ
	8 mm			48	25		12				25SFTF08SXZ
	9 mm			48	25		12				25SFTF09SXZ
	10 mm			48	25		12				25SFTF10SXZ
	13 mm			48	25		15				25SFTF13SXZ

The right plug in brass design can be found under series 26 from page 87.



	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	R 1/4	19		60	12		23			blank	25KBAK13BPX
	R 1/4	19		60	12		23			nickel plated	25KBAK13BPN
	R 3/8	19		59	10,5		23			blank	25KBAK17BPX
	R 3/8	19		59	10,5		23			nickel plated	25KBAK17BPN
	R 1/2	22		57,5	9		23			blank	25KBAK21BPX
	R 1/2	22		57,5	9		23			nickel plated	25KBAK21BPN
	M 14 x 1,5	19		59	10		23			blank	25KBAD14BPX
	M 14 x 1,5	19		59	10		23			nickel plated	25KBAD14BPN
	M 16 x 1,5	19		60	11		23			blank	25KBAD16BPX
	M 16 x 1,5	19		60	11		23			nickel plated	25KBAD16BPN
	M 18 x 1,5	19		60	11		23			blank	25KBAD18BPX
	M 18 x 1,5	19		60	11		23			nickel plated	25KBAD18BPN
 Female Thread	G 1/4	19		56	10		23			blank	25KBIW13BPX
	G 1/4	19		56	10		23			nickel plated	25KBIW13BPN
	G 3/8	19		55	9		23			blank	25KBIW17BPX
	G 3/8	19		55	9		23			nickel plated	25KBIW17BPN
	G 1/2	24		58	12		23			blank	25KBIW21BPX
	G 1/2	24		58	12		23			nickel plated	25KBIW21BPN
	M 16 x 1,5	19		55	9		23			blank	25KBIM16BPX
	M 16 x 1,5	19		55	9		23			nickel plated	25KBIM16BPN
	M 18 x 1,5	22		56	9		23			blank	25KBIM18BPX
	M 18 x 1,5	22		56	9		23			nickel plated	25KBIM18BPN
 Hose Barb	6 mm	19		74	25		23			blank	25KBTF06BPX
	6 mm	19		74	25		23			nickel plated	25KBTF06BPN
	8 mm	19		74	25		23			blank	25KBTF08BPX
	8 mm	19		74	25		23			nickel plated	25KBTF08BPN
	9 mm	19		74	25		23			blank	25KBTF09BPX
	9 mm	19		74	25		23			nickel plated	25KBTF09BPN
	10 mm	19		74	25		23			blank	25KBTF10BPX
	10 mm	19		74	25		23			nickel plated	25KBTF10BPN
	13 mm	19		74	25		23			blank	25KBTF13BPX
	13 mm	19		74	25		23			nickel plated	25KBTF13BPN
	10 mm Parker	19		73	24		23			blank	25KBTP10BPX
	10 mm Parker	19		73	24		23			nickel plated	25KBTP10BPN
	13 mm Parker	19		76	28		23			blank	25KBTP13BPX
	13 mm Parker	19		76	28		23			nickel plated	25KBTP13BPN
 with Plastic Hose Connection	8 x 10 mm	19		65	9	8	23		M 16 x 1	blank	25KBKO10BPX
	8 x 10 mm	19		65	9	8	23		M 16 x 1	nickel plated	25KBKO10BPN
	9 x 12 mm	19		65	9	8	23		M 16 x 1	blank	25KBKO12BPX
	9 x 12 mm	19		65	9	8	23		M 16 x 1	nickel plated	25KBKO12BPN



Coupling – with valve

Series 25KB

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Panel Mount with Hose Barb	6 mm	19	17	76	17	10	23	4	M 12 x 1	blank	25KBTS06BPX
	6 mm	19	17	76	17	10	23	4	M 12 x 1	nickel plated	25KBTS06BPN
	8 mm	19	17	80	17	14	23	4	M 12 x 1	blank	25KBTS08BPX
	8 mm	19	17	80	17	14	23	4	M 12 x 1	nickel plated	25KBTS08BPN
	10 mm	19	17	76	17	10	23	4	M 12 x 1	blank	25KBTS10BPX
	10 mm	19	17	76	17	10	23	4	M 12 x 1	nickel plated	25KBTS10BPN
 Plastic Hose Connection with Spring Guard	6 x 8 mm	19		144	7	6	23		M 12 x 1	blank	25KBKK08BPX
	6 x 8 mm	19		144	7	6	23		M 12 x 1	nickel plated	25KBKK08BPN
	9 x 12 mm	19		162	9	8	23		M 16 x 1	blank	25KBKK12BPX
	9 x 12 mm	19		162	9	8	23		M 16 x 1	nickel plated	25KBKK12BPN








Plugs – with valve

Series 25KB

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/8	22		44,5	9					blank	25SBAW10MPX
	G 1/8	22		44,5	9					nickel plated	25SBAW10MPN
	G 1/4	22		43	9					blank	25SBAW13MPX
	G 1/4	22		43	9					nickel plated	25SBAW13MPN
	G 3/8	22		43	9					blank	25SBAW17MPX
	G 3/8	22		43	9					nickel plated	25SBAW17MPN
	G 1/2	22		46	12					blank	25SBAW21MPX
	G 1/2	22		46	12					nickel plated	25SBAW21MPN
	M 14 x 1,5	22		44	10					blank	25SBAD14MPX
	M 14 x 1,5	22		44	10					nickel plated	25SBAD14MPN
	M 16 x 1,5	22		45	11					blank	25SBAD16MPX
	M 16 x 1,5	22		45	11					nickel plated	25SBAD16MPN
	M 18 x 1,5	22		45	11					blank	25SBAD18MPX
	M 18 x 1,5	22		45	11					nickel plated	25SBAD18MPN
 Female Thread	G 1/4	22		43	10					blank	25SBIW13MPX
	G 1/4	22		43	10					nickel plated	25SBIW13MPN
	G 3/8	22		43	9					blank	25SBIW17MPX
	G 3/8	22		43	9					nickel plated	25SBIW17MPN
	G 1/2	24		46	9					blank	25SBIW21MPX
	G 1/2	24		46	9					nickel plated	25SBIW21MPN
	M 14 x 1,5	22		43	9					blank	25SBIM14MPX
	M 14 x 1,5	22		43	9					nickel plated	25SBIM14MPN








	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Female Thread	M 16 x 1,5	22		43	9					blank	25SBIM16MPX
	M 16 x 1,5	22		43	9					nickel plated	25SBIM16MPN
	M 18 x 1,5	22		43	9					blank	25SBIM18MPX
	M 18 x 1,5	22		43	9					nickel plated	25SBIM18MPN
 Hose Barb	6 mm	21		60	25					blank	25SBTF06MPX
	6 mm	21		60	25					nickel plated	25SBTF06MPN
	8 mm	21		60	25					blank	25SBTF08MPX
	8 mm	21		60	25					nickel plated	25SBTF08MPN
	9 mm	21		60	25					blank	25SBTF09MPX
	9 mm	21		60	25					nickel plated	25SBTF09MPN
	10 mm	21		60	25					blank	25SBTF10MPX
	10 mm	21		60	25					nickel plated	25SBTF10MPN
	13 mm	21		60	25					blank	25SBTF13MPX
	13 mm	21		60	25					nickel plated	25SBTF13MPN
	6 mm Parker	19		67,5	20,5					blank	25SBTP06MPX
	6 mm Parker	19		67,5	20,5					nickel plated	25SBTP06MPN
	10 mm Parker	19		71	24					blank	25SBTP10MPX
	10 mm Parker	19		71	24					nickel plated	25SBTP10MPN
	13 mm Parker	19		83	28					blank	25SBTP13MPX
	13 mm Parker	19		83	28					nickel plated	25SBTP13MPN
 with Plastic Hose Connection	4 x 6 mm	21		47	7	6			M 10 x 1	blank	25SBKO06MPX
	4 x 6 mm	21		47	7	6			M 10 x 1	nickel plated	25SBKO06MPN
	6 x 8 mm	21		47	7	6			M 12 x 1	blank	25SBKO08MPX
	6 x 8 mm	21		47	7	6			M 12 x 1	nickel plated	25SBKO08MPN
	8 x 10 mm	21		51	8,5	8,5			M 16 x 1	blank	25SBKO10MPX
	8 x 10 mm	21		51	8,5	8,5			M 16 x 1	nickel plated	25SBKO10MPN
	9 x 12 mm	21		51	8,5	8,5			M 16 x 1	blank	25SBKO12MPX
	9 x 12 mm	21		51	8,5	8,5			M 16 x 1	nickel plated	25SBKO12MPN
 Panel Mount with Hose Barb	6 mm	21	17	62	17	10		4	M 12 x 1	blank	25SBTS06MPX
	6 mm	21	17	62	17	10		4	M 12 x 1	nickel plated	25SBTS06MPN
	8 mm	21	17	65	17	14		4	M 12 x 1	blank	25SBTS08MPX
	8 mm	21	17	65	17	14		4	M 12 x 1	nickel plated	25SBTS08MPN
	10 mm	21	17	74	25	14		3,5	G 1/4	blank	25SBTS10MPX
	10 mm	21	17	74	25	14		3,5	G 1/4	nickel plated	25SBTS10MPN
 Plastic Hose Connection with Spring Guard	4 x 6 mm	19		120	7	6			M 10 x 1	blank	25SBKK06MPX
	4 x 6 mm	19		120	7	6			M 10 x 1	nickel plated	25SBKK06MPN
	6 x 8 mm	19		135	7	6			M 12 x 1	blank	25SBKK08MPX
	6 x 8 mm	19		135	7	6			M 12 x 1	nickel plated	25SBKK08MPN
	8 x 10 mm	19		145	8,5	8,5			M 16 x 1	blank	25SBKK10MPX
	8 x 10 mm	19		145	8,5	8,5			M 16 x 1	nickel plated	25SBKK10MPN
	9 x 12 mm	19		150	8,5	8,5			M 16 x 1	blank	25SBKK12MPX
	9 x 12 mm	19		150	8,5	8,5			M 16 x 1	nickel plated	25SBKK12MPN









Coupling – flat-sealing

Series 25KL

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	R 1/4	19		60	12		23				25KLAK13BPN
	R 3/8	19		60	12		23				25KLAK17BPN
	R 1/2	22		61	17		23				25KLAK21BPN
 Female Thread	G 1/4	19		56	10		23				25KLIW13BPN
	G 3/8	19		55	9		23				25KLIW17BPN
	G 1/2	24		58	12		23				25KLIW21BPN
	M 14 x 1,5	19		55	9		23				25KLIM14BPN
	M 16 x 1,5	19		55	9		23				25KLIM16BPN
	M 18 x 1,5	22		56	9		23				25KLIM18BPN
 Hose Barb	6 mm	19		74	25		23				25KLTF06BPN
	8 mm	19		74	25		23				25KLTF08BPN
	9 mm	19		74	25		23				25KLTF09BPN
	10 mm	19		74	25		23				25KLTF10BPN
	13 mm	19		74	25		23				25KLTF13BPN
 with Plastic Hose Connection	6 x 8 mm	19		61	7	6	23		M 12 x 1		25KLKO08BPN
	8 x 10 mm	19		64,5	9	8	23		M 16 x 1		25KLKO10BPN
	9 x 12 mm	19		64,5	9	8	23		M 16 x 1		25KLKO12BPN
 Plastic Hose Connection with Spring Guard	6 x 8 mm	19		144	7	6	23		M 12 x 1		25KLKK08BPN
	8 x 10 mm	19		155	9	8	23		M 16 x 1		25KLKK10BPN
	9 x 12 mm	19		162	9	8	23		M 16 x 1		25KLKK12BPN



	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/4	22		43	9						25SLAW13MPN
	G 3/8	22		43	9						25SLAW17MPN
	G 1/2	22		46	12						25SLAW21MPN
	M 14 x 1,5	22		44	10						25SLAD14MPN
	M 16 x 1,5	22		45	11						25SLAD16MPN
	M 18 x 1,5	22		45	11						25SLAD18MPN
 Female Thread	G 1/4	22		43	10						25SLIW13MPN
	G 3/8	22		43	9						25SLIW17MPN
	G 1/2	24		46	12						25SLIW21MPN
	M 14 x 1,5	22		43	9						25SLIM14MPN
	M 16 x 1,5	22		43	9						25SLIM16MPN
	M 18 x 1,5	22		43	9						25SLIM18MPN
 Hose Barb	9 mm	21		60	25						25SLTF09MPN
	10 mm	21		60	25						25SLTF10MPN
	13 mm	21		60	25						25SLTF13MPN
 with Plastic Hose Connection	6 x 8 mm	21		47	7	6			M 12 x 1		25SLKO08MPN
	8 x 10 mm	21		51	8,5	8,5			M 16 x 1		25SLKO10MPN
	9 x 12 mm	21		51	8,5	8,5			M 16 x 1		25SLKO12MPN
 Panel Mount with Hose Barb	6 mm	21	17	62	17	10		4	M 12 x 1		25SLTS06MPN
	10 mm	21	7	74	25	14		3,5	G 1/4		25SLTS10MPN
 Plastic Hose Connection with Spring Guard	6 x 8 mm	19		135	7	6			M 12 x 1		25SLKK08MPN
	8 x 10 mm	19		145	8,5	8,5			M 16 x 1		25SLKK10MPN
	9 x 12 mm	19		150	8,5	8,5			M 16 x 1		25SLKK12MPN

Nominal Diameter

7,4 = 42 mm²

Rectus Series

25



Other designs in series 25

The following other designs can be found from page:

- | | |
|-----------------------|--------|
| ► Brass / Steel | P. 98 |
| ► Safety | P. 274 |
| ► Safety Self-Venting | P. 294 |
| ► Coded Systems | P. 302 |

Technical Description

Universal industrial coupling with standard European profile for use with gaseous, liquid and aggressive media.

Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use. The collar design minimises damage to the valve body.






Dust Protections (P. 319)

for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S






Working Temperature*

-15°C up to +200°C (FKM)
depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.

 KA Single Shut-Off	 KB Double Shut-Off	 KL Leak-Free
Working Pressure** 35 bar ** maximum static working pressure with safety factor 4 to 1.	35 bar	8 bar
Features		• Minimal, almost imperceptible leakage when uncoupling • No air locked into the system during the coupling process
Material Coupling: AISI 303 / AISI 316 L Plug: AISI 303 / AISI 316 L Seals: FKM	Coupling: AISI 303 / AISI 316 L Plug: AISI 303 / AISI 316 L Seals: FKM	Coupling: AISI 303 / AISI 316 L Plug: AISI 303 / AISI 316 L Seals: FKM
Interchangeability • Rectus 26 • Cejn 320 • various German Products		
Flow diagrams Air  Water 	Air  Water 	Water 







	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/4	19		59,5	10,5		23			AISI 303	25KAAW13RVX
	G 1/4	19		59,5	10,5		23			AISI 316 L	25KAAW13EVX
	G 3/8	19		57,5	9		23			AISI 303	25KAAW17RVX
	G 3/8	19		57,5	9		23			AISI 316 L	25KAAW17EVX
	G 1/2	24		60,5	12		23			AISI 303	25KAAW21RVX
	G 1/2	24		60,5	12		23			AISI 316 L	25KAAW21EVX
	M 18 x 1,5	19		59,5	11		23			AISI 303	25KAAM18RVX
 Female Thread	G 1/4	19		55,5	10		23			AISI 303	25KAIW13RVX
	G 1/4	19		55,5	10		23			AISI 316 L	25KAIW13EVX
	G 3/8	19		54,5	9		23			AISI 303	25KAIW17RVX
	G 3/8	19		54,5	9		23			AISI 316 L	25KAIW17EVX
	G 1/2	24		57,5	12		23			AISI 303	25KAIW21RVX
	G 1/2	24		57,5	12		23			AISI 316 L	25KAIW21EVX
 Hose Barb	6 mm	19		73,5	25		23			AISI 303	25KATF06RVX
	6 mm	19		73,5	25		23			AISI 316 L	25KATF06EVX
	8 mm	19		73,5	25		23			AISI 303	25KATF08RVX
	8 mm	19		73,5	25		23			AISI 316 L	25KATF08EVX
	9 mm	19		73,5	25		23			AISI 303	25KATF09RVX
	9 mm	19		73,5	25		23			AISI 316 L	25KATF09EVX
	10 mm	19		73,5	25		23			AISI 303	25KATF10RVX
	10 mm	19		73,5	25		23			AISI 316 L	25KATF10EVX
	13 mm	19		73,5	25		23			AISI 303	25KATF13RVX
	13 mm	19		73,5	25		23			AISI 316 L	25KATF13EVX
 with Plastic Hose Connection	6 x 8 mm	19		61	7	6	23		M 12 x 1	AISI 303	25KAKO08RVX
	6 x 8 mm	19		61	7	6	23		M 12 x 1	AISI 316 L	25KAKO08EVX
	8 x 10 mm	19		64,5	9	8	23		M 16 x 1	AISI 303	25KAKO10RVX
	9 x 12 mm	19		64,5	9	8	23		M 16 x 1	AISI 303	25KAKO12RVX
	9 x 12 mm	19		64,5	9	8	23		M 16 x 1	AISI 316 L	25KAKO12EVX
 Panel Mount with Hose Barb	6 mm	19	17	75,5	17	10	23	4	M 12 x 1	AISI 303	25KATS06RVX
	8 mm	19	17	79,5	17	14	23	4	M 12 x 1	AISI 303	25KATS08RVX
	10 mm	19	19	79,5	25	14	23	4	M 14 x 1	AISI 303	25KATS10RVX








Plugs – without valve

Series 25KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 3/8	19		33	9					AISI 303	25SFAW17RXX
	G 3/8	19		33	9					AISI 316 L	25SFAW17EXX
	G 1/2	24		38	12					AISI 303	25SFAW21RXX
	G 1/2	24		38	12					AISI 316 L	25SFAW21EXX
 Female Thread	G 1/8	14		30	7					AISI 303	25SFIW10RXX
	G 1/8	14		30	7					AISI 316 L	25SFIW10EXX
	G 1/4	17		33	10					AISI 303	25SFIW13RXX
	G 1/4	17		33	10					AISI 316 L	25SFIW13EXX
	G 3/8	19		33	10					AISI 303	25SFIW17RXX
	G 3/8	19		33	10					AISI 316 L	25SFIW17EXX
	G 1/2	24		35	12					AISI 303	25SFIW21RXX
	G 1/2	24		35	12					AISI 316 L	25SFIW21EXX
 Hose Barb	M 16 x 1,5	19		33	10					AISI 303	25SFIM16RXX
	6 mm			48	25		12			AISI 303	25SFTF06RXX
	6 mm			48	25		12			AISI 316 L	25SFTF06EXX
	8 mm			48	25		12			AISI 303	25SFTF08RXX
	8 mm			48	25		12			AISI 316 L	25SFTF08EXX
	9 mm			48	25		12			AISI 303	25SFTF09RXX
	9 mm			48	25		12			AISI 316 L	25SFTF09EXX
	10 mm			48	25		12			AISI 303	25SFTF10RXX
	10 mm			48	25		12			AISI 316 L	25SFTF10EXX
 with Plastic Hose Connection	13 mm			48	25		15			AISI 303	25SFTF13RXX
	13 mm			48	25		15			AISI 316 L	25SFTF13EXX
	4 x 6 mm			34	7	6	12		M 10 x 1	AISI 303	25SFKO06RXX
	4 x 6 mm			34	7	6	12		M 10 x 1	AISI 316 L	25SFKO06EXX
	6 x 8 mm			34	7	6	12		M 12 x 1	AISI 303	25SFKO08RXX
	6 x 8 mm			34	7	6	12		M 12 x 1	AISI 316 L	25SFKO08EXX
	8 x 10 mm	17		42	9	8			M 16 x 1	AISI 303	25SFKO10RXX








	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/4	19		59,5	10,5		23			AISI 303	25KBAW13RVX
	G 1/4	19		59,5	10,5		23			AISI 316 L	25KBAW13EVX
	G 3/8	19		57,5	9		23			AISI 303	25KBAW17RVX
	G 3/8	19		57,5	9		23			AISI 316 L	25KBAW17EVX
	G 1/2	24		60,5	12		23			AISI 303	25KBAW21RVX
	G 1/2	24		60,5	12		23			AISI 316 L	25KBAW21EVX
	M 16 x 1,5	19		59	10,5		23			AISI 303	25KBAM16RVX
	M 16 x 1,5	19		59	10,5		23			AISI 316 L	25KBAM16EVX
 Female Thread	G 1/4	19		55,5	10		23			AISI 303	25KBIW13RVX
	G 1/4	19		55,5	10		23			AISI 316 L	25KBIW13EVX
	G 3/8	19		54,5	9		23			AISI 303	25KBIW17RVX
	G 3/8	19		54,5	9		23			AISI 316 L	25KBIW17EVX
	G 1/2	24		57,5	12		23			AISI 303	25KBIW21RVX
	G 1/2	24		57,5	12		23			AISI 316 L	25KBIW21EVX
	M 14 x 1,5	19		54,5	9		23			AISI 303	25KBIM14RVX
	M 16 x 1,5	19		54,5	9		23			AISI 303	25KBIM16RVX
	M 18 x 1,5	22		54,5	9		23			AISI 303	25KBIM18RVX
 Hose Barb	6 mm	19		73,5	25		23			AISI 303	25KBTF06RVX
	6 mm	19		73,5	25		23			AISI 316 L	25KBTF06EVX
	8 mm	19		73,5	25		23			AISI 303	25KBTF08RVX
	8 mm	19		73,5	25		23			AISI 316 L	25KBTF08EVX
	9 mm	19		73,5	25		23			AISI 303	25KBTF09RVX
	9 mm	19		73,5	25		23			AISI 316 L	25KBTF09EVX
	10 mm	19		73,5	25		23			AISI 303	25KBTF10RVX
	10 mm	19		73,5	25		23			AISI 316 L	25KBTF10EVX
	13 mm	19		73,5	25		23			AISI 303	25KBTF13RVX
	13 mm	19		73,5	25		23			AISI 316 L	25KBTF13EVX
 with Plastic Hose Connection	6 x 8 mm	19		61	7	6	23		M 12 x 1	AISI 303	25KBKO08RVX
	6 x 8 mm	19		61	7	6	23		M 12 x 1	AISI 316 L	25KBKO08EVX
	8 x 10 mm	19		64,5	9	8	23		M 16 x 1	AISI 303	25KBKO10RVX
	9 x 12 mm	19		64,5	9	8	23		M 16 x 1	AISI 303	25KBKO12RVX
	9 x 12 mm	19		64,5	9	8	23		M 16 x 1	AISI 316 L	25KBKO12EVX
 Panel Mount with Hose Barb	10 mm	19	19	79,5	25	14	23	4	M 14 x 1	AISI 303	25KBTS10RVX



Plugs – with valve




Series 25KB

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/8	19		54	7					AISI 303	25SBAW10RVX
	G 1/8	19		54	7					AISI 316 L	25SBAW10EVX
	G 1/4	19		58	10,5					AISI 303	25SBAW13RVX
	G 1/4	19		58	10,5					AISI 316 L	25SBAW13EVX
	G 3/8	19		56	9					AISI 303	25SBAW17RVX
	G 3/8	19		56	9					AISI 316 L	25SBAW17EVX
	G 1/2	24		59	12					AISI 303	25SBAW21RVX
	G 1/2	24		59	12					AISI 316 L	25SBAW21EVX
	M 16 x 1,5	19		57,5	10,5					AISI 303	25SBAM16RVX
	M 16 x 1,5	19		57,5	10,5					AISI 316 L	25SBAM16EVX
 Female Thread	M 18 x 1,5	19		58	11					AISI 303	25SBAM18RVX
	G 1/4	19		54	10					AISI 303	25SBIW13RVX
	G 1/4	19		54	10					AISI 316 L	25SBIW13EVX
	G 3/8	19		53	9					AISI 303	25SBIW17RVX
	G 3/8	19		53	9					AISI 316 L	25SBIW17EVX
	G 1/2	24		56	12					AISI 303	25SBIW21RVX
	G 1/2	24		56	12					AISI 316 L	25SBIW21EVX
 Hose Barb	M 18 x 1,5	22		53	9					AISI 303	25SBIM18RVX
	6 mm	19		72	25					AISI 303	25SBTF06RVX
	6 mm	19		72	25					AISI 316 L	25SBTF06EVX
	8 mm	19		72	25					AISI 303	25SBTF08RVX
	8 mm	19		72	25					AISI 316 L	25SBTF08EVX
	9 mm	19		72	25					AISI 303	25SBTF09RVX
	9 mm	19		72	25					AISI 316 L	25SBTF09EVX
	10 mm	19		72	25					AISI 303	25SBTF10RVX
	10 mm	19		72	25					AISI 316 L	25SBTF10EVX
	13 mm	19		72	25					AISI 303	25SBTF13RVX
	13 mm	19		72	25					AISI 316 L	25SBTF13EVX
 with Plastic Hose Connection	4 x 6 mm	19		59	7	6			M 10 x 1	AISI 303	25SBKO06RVX
	6 x 8 mm	19		59	7	6			M 12 x 1	AISI 303	25SBKO08RVX
	6 x 8 mm	19		59	7	6			M 12 x 1	AISI 316 L	25SBKO08EVX
	8 x 10 mm	19		63	8,5	8,5			M 16 x 1	AISI 303	25SBKO10RVX
	9 x 12 mm	19		63	8,5	8,5			M 16 x 1	AISI 303	25SBKO12RVX
	9 x 12 mm	19		63	8,5	8,5			M 16 x 1	AISI 316 L	25SBKO12EVX
 Panel Mount with Hose Barb	6 mm	19	17	74	17	10			M 12 x 1	AISI 303	25SBTS06RVX
	8 mm	19	17	78	17	14			M 12 x 1	AISI 303	25SBTS08RVX
	10 mm	19	19	78	17	14			M 14 x 1	AISI 303	25SBTS10RVX



Couplings – flat-sealing




Series 25KL

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/4	19		59,5	10,5		23			AISI 303	25KLAW13RVX
	G 1/4	19		59,5	10,5		23			AISI 316 L	25KLAW13EVX
	G 3/8	19		57,5	9		23			AISI 303	25KLAW17RVX
	G 3/8	19		57,5	9		23			AISI 316 L	25KLAW17EVX
	G 1/2	24		60,5	12		23			AISI 303	25KLAW21RVX
	G 1/2	24		60,5	12		23			AISI 316 L	25KLAW21EVX
 Female Thread	G 1/4	19		55,5	10		23			AISI 303	25KLIW13RVX
	G 1/4	19		55,5	10		23			AISI 316 L	25KLIW13EVX
	G 3/8	19		54,5	9		23			AISI 303	25KLIW17RVX
	G 3/8	19		54,5	9		23			AISI 316 L	25KLIW17EVX
	G 1/2	24		57,5	12		23			AISI 303	25KLIW21RVX
	G 1/2	24		57,5	12		23			AISI 316 L	25KLIW21EVX
 Hose Barb	9 mm	19		73,5	25		23			AISI 303	25KLTF09RVX
	9 mm	19		73,5	25		23			AISI 316 L	25KLTF09EVX
	13 mm	19		73,5	25		23			AISI 303	25KLTF13RVX
	13 mm	19		73,5	25		23			AISI 316 L	25KLTF13EVX



Plugs – flat-sealing

Series 25KL

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 Male Thread	G 1/4	19		58	10,5					AISI 303	25SLAW13RVX
	G 1/4	19		58	10,5					AISI 316 L	25SLAW13EVX
	G 3/8	19		56	9					AISI 303	25SLAW17RVX
	G 3/8	19		56	9					AISI 316 L	25SLAW17EVX
	G 1/2	24		59	12					AISI 303	25SLAW21RVX
	G 1/2	24		59	12					AISI 316 L	25SLAW21EVX
 Female Thread	G 1/4	19		54	10					AISI 303	25SLIW13RVX
	G 1/4	19		54	10					AISI 316 L	25SLIW13EVX
	G 3/8	19		53	9					AISI 303	25SLIW17RVX
	G 3/8	19		53	9					AISI 316 L	25SLIW17EVX
	G 1/2	24		56	12					AISI 303	25SLIW21RVX
	G 1/2	24		56	12					AISI 316 L	25SLIW21EVX
 Hose Barb	6 mm	19		75	25					AISI 303	25SLTF06RVX
	9 mm	19		72	25					AISI 303	25SLTF09RVX
	9 mm	19		72	25					AISI 316 L	25SLTF09EVX
	13 mm	19		72	25					AISI 303	25SLTF13RVX
	13 mm	19		72	25					AISI 316 L	25SLTF13EVX