

New from Parker!

- Compatible with R12, R22 and R134a
- Utilizes three series of Parker fittings
- Parkrimp compatible

Product Bulletin

Parker 285 Air Conditioning Hose



Bulletin No. 4480-B37-USA December, 1999

Parker Hannifin Corporation
Hose Products Division
30240 Lakeland Blvd., Wickliffe, Ohio 44092
Phone: (440) 943-5700 • Fax: (440) 943-3129
www.parkerhose.com

Parker
FluidConnectors

Parker 285 is the one air conditioning hose that keeps you cool two ways

Whether your requirement is for permanent or field attachable assemblies – or both – Parker 285 is the high-performance air conditioning hose designed to keep you cool both ways.



Application flexibility

Parker 285 provides solutions for R12, R22, and R134a applications. And you can use your choice of Parker 26 Series permanent or 21 and 23 Series field attachable fittings.

New construction

Parker 285 features an elastomeric inner tube that creates a tight, high-integrity seal between hose and fitting. A nylon barrier provides low refrigerant permeation, while the tough elastomeric outer cover

inhibits moisture ingress and protects from heat and ozone.

Parkrimp compatible

Parker 285 hose and permanent fittings are compatible with the Parkrimp system of crimpers. So assembly is as simple as 1-2-3.

26 Series fittings: when versatility really matters

Parker 26 Series fittings feature over 25 different end configurations. So no matter where you need to go, 26 Series fittings will get you there. Plus, they can be used on virtually all 100R5 type hoses. Simpler really is better.



All Parker steel fittings feature a durable, corrosion-resistant zinc plating.



Phastkrimp



Karrykrimp



Karrykrimp 2



Parkrimp 1



Superkrimp



Parkrimp 2

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Burst Pressure		Minimum Bend Radius		Weight		Inches of Hg		Crimp Series	Field Attachable Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	kg/m	of Hg	kPa		
285-4	3/16	5	0.49	12	400	2,7	2000	13,7	1	25	0.093	0.14	28	6	26	21,23
285-6	5/16	8	0.62	16	400	2,7	2000	13,7	1 1/2	38	0.125	0.19	28	6	26	21,23
285-8	13/32	10	0.74	19	400	2,7	2000	13,7	2	51	0.168	0.25	28	6	26	21,23
285-10	1/2	12,5	0.83	21	400	2,7	2000	13,7	2 1/2	64	0.180	0.27	28	6	26	21,23
285-12	5/8	16	0.96	24	400	2,7	2000	13,7	3	76	0.228	0.34	28	6	26	21,23

DANGER

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

Before selecting or using any Parker hose or fittings or related accessories, it is important that you read and follow Parker Safety Guide for Selecting and Using Hoses, Fittings, and Related Accessories (Parker Publication No. 4400-B.1).

Distributed by:

信德迈公司2012年开始派克签约分销商: 信德迈科技(北京)有限公司
北京朝阳区望京 SOHO-T1-C 座2115 室 邮编:100102
手机: 139 1096 2635 电子邮件: sales@cnmec.biz

The World Standard



Bulletin 4480-B37-USA QDI 10M 12/99
©1999 Parker Hannifin Corporation