

# 929/929B – Heavy Wall PTFE Hose



## Features

- Tight bend radius
- Excellent kink resistance
- Enhanced resistance to gas permeation due to increased PTFE wall thickness (.040")

## Certifications

- Meets or Exceeds SAE 100R14A - 929
- Meets or Exceeds SAE 100R14B - 929B
- FDA CFR 177.1550 (Natural tube)

## Applications/Markets



- Chemical transfer lines
- General hydraulics
- Compressed air/gases
- Adhesive dispensing
- Coolant Lines
- Medical Gases
- 919 (100R14) hose applications requiring tight routings

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
929-4	929B-4	3/16	5	.34	9	3,000	20.7	2.00	51	28	.08	.12	91N
929-6	929B-6	5/16	8	.47	12	2,500	17.2	4.00	102	28	.12	.18	91N
929-8	929B-8	13/32	10	.59	15	2,000	13.8	4.60	117	28	.16	.23	91N
-	929B-12	5/8	16	.81	21	1,200	8.3	6.50	165	12	.19	.28	91N
-	929B-16	7/8	22	1.14	29	1,250	8.6	7.40	188	12	.49	.73	91N

## Construction

Tube: 929 - Natural FDA Compliant PTFE  
 929B - Black Static-Dissipative PTFE  
 Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:  
 -100°F to +450°F (-73°C to +232°C)  
 Change in length at working pressure is +2% to -4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

91N Series – pg. E-52  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Use hose type 929B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.