

# Snap-tite GF-Series

Quick Couplings for Natural & Propane Gas

## CSA and ANSI Approved brass coupling

Parker Snap-tite's GF/GF-1 Series couplings are designed for use on small gas appliances. They are valved on the coupler half and will automatically shut off gas flow when coupling is disconnected and automatically open on connection.

They also incorporate a safety fuse in the nipple that will shut off the gas supply to your application in the event temperatures exceed 177°C.



## Contact Information:

Parker Hannifin Manufacturing  
Sweden AB  
**Quick Coupling Division Europe**  
Västra Skogsrovägen 1  
54106 Skövde – Sweden

phone +46 500 44 36 00  
fax +46 500 44 36 20  
tema-rfq@parker.com

[www.parker.com](http://www.parker.com)

## GF-Series Features:

- Brass construction
- Superior flow capacity
- 1/2 psi max pressure rating
- 1/4" - 1 1/4" size range
- Fusible link internal to the nipple protects against gas-fed fires
- Certified to ANSI Z21-41-2011, CSA 6.9-2011 for use with natural, manufactured and mixed gases, liquefied petroleum gases and LP gas-air mixtures



ENGINEERING YOUR SUCCESS.

# Technical and Dimensional Information


## Specifications GF-Series

Body Size	1/4	3/8	1/2	3/4	1	1 1/4
Flow Capacity*	24,300 Btu/hr	50,000 Btu/hr	99,600 Btu/hr	212,000 Btu/hr	378,000 Btu/hr	475,000 Btu/hr


**Temperature Range:** Standard GF/GF-1 (indoor use) temperature range: 32°F up to +200°F (0°C up to +93°C).  
Contact QCDE Sales Team for low temperature version (outdoor use) temperature range: -40°F up to +200°F (-40°C up to +93°C).  
Coupler part number suffixed with "L".

\* Based on a 1000 Btu per cubic foot gas with a specific gravity of 0.64 at a pressure drop of 0.3 in w.c.

## Coupling

	Body Size	Part Number Brass	Connection	Length mm	Connected Length mm	Largest Diameter mm	Wrench Flats mm	Weight (lbs)
	1/4	BVGFC4-4F	1/4-18 NPTF	41,66	61,21	24,38	22,35	0.194
	3/8	BVGFC6-6F	3/8-18 NPTF	48,26	68,33	30,99	25,40	0.284
	1/2	BVGF-1C8-8F	1/2-14 NPTF	62,74	86,11	36,07	25,40	0.326
	3/4	BVGF-1C12-12F	3/4-14 NPTF	63,75	88,39	42,16	33,27	0.534
	1	BVGFC16-16F	1-11 1/2 NPTF	68,33	99,31	51,56	47,75	1.150
	1 1/4	BVGFC20-20F	1 1/4-11 1/2 NPTF	89,92	123,95	57,15	50,80	1.568

## Plug

	Body Size	Part Number Brass	Connection	Length mm	Connected Length mm	Largest Diameter mm	Wrench Flats mm	Weight (lbs)
	1/4	BPGFN4-4F	1/4-18 NPTF	33,53	61,21	17,53	15,75	0.052
	3/8	BPGFN6-6F	3/8-18 NPTF	38,61	68,33	23,11	20,57	0.105
	1/2	BPGF-1N8-8F	1/2-14 NPTF	39,37	86,11	28,70	25,40	0.154
	3/4	BPGF-1N12-12F	3/4-14 NPTF	45,47	88,39	34,04	30,23	0.212
	1	BPGFN16-16F	1-11 1/2 NPTF	53,34	99,31	41,91	38,10	0.380
	1 1/4	BPGFN20-20F	1 1/4-11 1/2 NPTF	56,39	123,95	52,32	47,75	0.576

2012年开始Snap-Tite签约中国代理商: 信德迈科技(北京)有限公司

地址: 北京朝阳区望京 SOHO-T1-C 座 2115 室 邮编:100102

手机: 139 1096 2635 电子邮件: sales@cnmec.biz

### Parker Hannifin Manufacturing Sweden AB

Quick Coupling Division Europe  
Västra Skogsrovägen 1  
54106 Skövde – Sweden  
Phone +46 500 44 36 00  
Fax +46 500 44 36 20  
www.parker.com

